

Aqua Multiseal GP is a grey coloured ready to use general purpose Acrylic sealing paste.

WHERE TO USE:

Aqua Multiseal GP is widely used to fill gaps and joints around doors, windows, fixtures and fitting or any other joints where limited amount of movement is expected. It is most successful compound between different building materials.

HOW TO USE:

Before application surface should be clean from dust, dirt, grease, oil or any other surface contaminations, first apply primer which is available in same container. Then Supermix paste & apply by hand & pack properly clean by sponge and potable water.

6 ADVANTAGES:

- Odourless can be painted over it.
- High UV resistant
- Ready to use-no mixing
- Attractive & Convenient Packings
- Strong adhesion to the most building material
- Not suitable on soft plastic, bare metals, bitumen or tar and also for any
- other under water joints.

PACKING: 500gm & 1 kg Containers

SHELF LIFE: 12 months if unopened

STORAGE: In cool place

SPECIFICATION:

Aqua Multiseal GP is grey in colour but any other colour could be made available on request. (Minimum Quantity 20 kg)

Movement 10 to 12% of average joint Depth – 6mm

Minimum Joint Depth – 6mm


Maximum Joint Width – 25 mm.

Width / Depth ration for joints upto 10 mm wide 1:1

Width/Depth ratio for joints between 10 mm and 25 mm wide 2:1.

DENSITY:

1.60 KG/L



APPLICATION TEMPERATURE:

Between 5c to 40 c

PRIMER: Use **Aqua Multeseal GP** primer all surfaces @ coverage 5 to 8 m per kg of primer (It is in same pack)

WARRANTY:

All products should be used in accordance with manufacturer's instruction. No responsibility will be taken by the manufacturer where conditions of use are beyond our control.

PRECAUTION:

All products should be used in accordance with manufacturer instructions. No responsibility will be taken by manufacturer where conditions of use differ from manufacturers instruction. The coverage figure/yield etc. are given for guidance only and actual field trials are recommended to ascertain the exact consumption/ Coverage.

IMPORTANT NOTE: As parameter, such as temperature, humidity and water addition change from site to site, the above instructions should be taken only as general guidelines. Performance of product depends on strict adherence to Aqua Proof guidelines. Aqua Proof will not be responsible for failure due to improper usage/application. The coverage/yield is given for guidance only and actual field trails are recommended to ascertain the exact coverage/yield.



Manufactured & Marketed by,
AQUAPROOF GROUP
A-302, Samarth Complex, Jawahar Nagar,
Goregaon (W), Mumbai 400 062. Maharashtra.

Customer Helpline: 022-28782493

Email: info@aquaproofindia.com

DISTRIBUTOR/DEALER

--